

CONTROL STATIONS

2121B-P SERIES

CONTROL STATIONS FOR AE SERIES LARGE DISPLAYS



2121B-P

The 2121B-P Control Station has a large red, momentary push button switch. Ideal for Start/Stop, Increment, Count, and Reset functions

Contact Rating: 2 Amps @ 48 VDC,
6 Amps @ 120 VAC

Wiring: Terminal screws on contact block inside. Compression fitting for up to 3/8" Dia. cable. Cable not included.

Specify Label: Start/Stop, Reset, Increment, Decrement, or custom.

The 2122B-P Control Station has a keylock switch for application where only a key operator has the authority to control Reset and Run functions.

Contact rating: 4 Amps @ 120 VAC or 28 VDC.

Wiring: Pigtail lead wires inside, terminate with wire nuts to incoming cable. Compression fitting for up to 3/8" Dia cable. Cable not included

Specify Label: Run/Reset, On/Off, or custom.

Enclosures: All models have a gray, flame retardant ABS plastic enclosure with mounting tabs. Dimensions: 4.6" x 4.6" x 2.3". Surface mounts to a wall or panel .

Optional: Two Conductor #22 for low voltage applications. Order ATS P/N:1380-8442

Cable /ft Power Cable, 18-3 SJT-3, Black for 120 VAC applications. Order ATS P/N: 1385-19348



2122B-P



**APPLIED
TECHNICAL
SYSTEMS**

800-444-7161

BOX 5705 • SHREVEPORT, LOUISIANA. 71135

FAX: 318-797-4864
www.ats-usa.com
phone: 318-797-7508