

PRODUCTION MONITORS AE44-503C SERIES



AE44-503C
Dual Line Display

MONITOR PRODUCTION "GOAL" and "ACTUAL" PERFORMANCE

Four-Inch High, LED Digits
Red for Goal, Green for Actual
Visible up to 150 feet.

Rugged Steel Enclosure
24"W x 18"H x 4"D

EASILY CONFIGURED TO YOUR NEEDS. .

Used with the AE-503DX1 Remote Display Interface

The AE-503DX1 provides a programmable pace that automatically paces the "GOAL" display, a RUN/HOLD switch to hold the pace during breaks or down periods, and separate RESET buttons for both the GOAL and ACTUAL displays. Count Up and Count Down push-buttons or signals are connected to the AE-503DX1. It then sends all data to the AEXX-503C Displays at distances up to 2000 feet away. The RS485 I/O port allows it to be connected to a PC for data acquisition (Requires AEQuery Software).



AE-503DX1 Controller

Used with your Computer or PLC

The "GOAL" and "ACTUAL" counts can be sent via RS232 from your Computer or PLC to the display, up to 2000 feet away. Uses the same data signal as the popular AE Series Option 354 Displays. The AE-503DX1 is not required for this system.

Other digit sizes and configurations are also available. Call us with your specifications.

TWO YEAR WARRANTY



**APPLIED
TECHNICAL
SYSTEMS**

800-444-7161

BOX 5705 • SHREVEPORT, LOUISIANA. 71135

FAX: 318-797-4864

www.ats-usa.com

phone: 318-797-7508