



SPECIFICATIONS:

ANODIZED ALUMINUM ENCLOSURE
 FIVE DIGITS, 8" HIGH, 7 SEGMENT
 1000 MCD RED LEDS VISIBLE UP TO 200 FEET
 OPTIONAL GREEN 60 MCD LEDS
 1/8" ACRYLIC FILTER, 1/8" BLACK ABS BACK PANEL
 120VAC OPERATION, OTHER POWER OPTIONAL
 TWO MOUNTING BRACKETS AT 8" CENTERS STANDARD
 (OPTIONAL MOUNTING AVAILABLE)
 PIGTAIL LEAD WIRES (18GA.) STANDARD

APPLICATIONS:

ELAPSED TIME INDICATORS, COUNT DOWN TIMERS
 PRESET TIMERS, RS232 INTERFACE
 MASTER/SLAVE DISPLAY

		VCAD LTRATS DWGSAEVAE 8X	
PROJECT:		P.O. BOX 5705 SHREVEPORT, LA 71155	
APPROVALS:		SCALE 1:6	
DRAWN BY: JLT	DATE: 8-14-01	DESIGNED BY:	CHECKED BY:
APPROVED BY:	DATE:	DRAWING: AE85-	REVISED:
DESCRIPTION: ASSEMBLY		DRAWING #	