



SPECIFICATIONS:

ENCLOSURE: (BOX .062 STEEL, FRONT PANLE .040 STEEL) BLACK POLANE TEXTURE
 0.5"x2.5" LCD DISPLAY
 OPERATES FROM EITHER 120VAC 60Hz OR 12VDC
 KEYHOLE MOUNTING ON BACK PANEL
 FOUR SPDT RELAY RATED AT 15A RESISTIVE AT 120VAC OR 28VDC
 AUTO PROMPTING FEATURE GUIDES USER THROUGH SETUP PROCESS
 UP TO 200 PROGRAM STEPS AND UP TO 20 ANNUAL PLANS
 PROGRAMMABLE DAYLIGHT SAVINGS TIME ADJUSTMENT
 AUTOMATIC LEAP YEAR COMPENSATION
 OUTPUT RELAYS MAY BE MANUALLY ENERGIZED AND DE-ENERGIZED
 SELECTED OUTPUTS MAY BE PULSED FROM 1 TO 99 SECONDS
 OPTIONAL PROGRAM TRANSFER AND PRINTOUT

APPROVALS	DATE
DRAWN BY DTI	8-13-01
CHECKED BY	
APPROVED BY	

VCAD LTV\ATS DWG\NAP MC\41_81\		APPLIED TECHNICAL SYSTEMS		P.O. BOX 5705 SHREVEPORT, LA 71135
PROJECT	MC41	SCALE	1:3	
DESCRIPTION	FINISHED GOOD	JOB #		
		SHEET #		
		REVISION		
		FILENAME	MC41FG1	
		DRAWING #		